

# Electric Automated Butterfly Valve

American Wheatley offers electric actuated butterfly valves with many available options.

## Features:

- Available 2" through 12"
- EPDM seats standard, Buna, PTFE and Viton available special request
- Voltages available: 115/60/1, 230/60/3
- Double acting or spring return models available
- NEMA 4
- Powder coated aluminum body for severe duty applications
- Stainless steel fasteners
- ISO 5211 mounting standard
- If necessary, all packages are direct mount if possible, or supplied with carbon steel bracket and coupler.



## Double Acting:

Available 2" through 12"  
 Cycle time 12-15 second  
 Available double acting, for on/off service  
 Option: 4-20mA control for modulating service  
 Spring return option available - call for pricing  
 Worm gear type, brake not required

Above with standard double acting actuators and butterfly valve with EPDM seats.  
 Consult factory for other options, voltages, and spring return assemblies.

SIZE	LUG STYLE	WAFER STYLE	VOLTAGE	ON/OFF
2	BFL02EW110	BFW02EW110	120/60/1	ON/OFF
2.5	BFL25EW110	BFW25EW110	120/60/1	ON/OFF
3	BFL03EW110	BFW03EW110	120/60/1	ON/OFF
4	BFL04EW110	BFW04EW110	120/60/1	ON/OFF
5	BFL05EW110	BFW05EW110	120/60/1	ON/OFF
6	BFL06EW110	BFW06EW110	120/60/1	ON/OFF
8	BFL08EW110	BFW08EW110	120/60/1	ON/OFF
10	BFL10EW110	BFW10EW110	120/60/1	ON/OFF
12	BFL12EW110	BFW12EW110	120/60/1	ON/OFF

All packaging materials, thread protectors, plastic plugs and caps must be removed before installation.

Dimensions are subject to change without notice, please confirm actual dimensions with factory at time of order.

JOB NAME _____
LOCATION _____
_____
CONTRACTOR _____
CONTRACTOR P.O. NO. _____

ITEMS	QUANTITY
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____



2701 W. Concord Street  
 Broken Arrow, OK 74012  
 Toll Free: 866-204-5229  
 PH: 918-317-0401  
 FAX: 918-317-0407  
 www.wheatleyhvac.com  
 e-mail: sales@globalflowproducts.com